

LED WALL PACK



Half Cutoff Style

LED Wall Pack lights provide a high-efficient 140 LPW and CCT & Wattage selectable in the field for the perimeter and security lighting. In addition, DLC-qualified LED luminaires are able to accelerate the payback.

 Std. 1-10vdc Dimming	 High Efficacy 140 LPW	 CCT & Wattage Selectable	 Emergency Backup Available	 IP65 Rated Waterproof
---	--	---	--	--

FEATURE

Style	Half Cutoff
Housing	Die-casting Aluminum Alloy
Diffuser	Impact-proof Glass 5mm thickness or PC
Waterproof	IP65
Lumen Efficacy	140 LPW
Wattage	Field Selectable
Color Temperature	Field Selectable
Motion Sensor	Occupancy
Photocell	Available
Emergency Backup Available	UL924, CEC Title-20
Listed	DLC, ETL/cETL, CE, RoHS
Warranty	5 Years

SPECIFICATION

Model#	Input Voltage	Wattage	CCT	Beam Angle	Size	Eqv.
LT-WP01-40W	100-277VAC	40W	30K, 40K, 50K, 57K	120	365*230*195mm	75-100W MH
LT-WP01-60W	100-277VAC	60W	30K, 40K, 50K, 57K	120	365*230*195mm	175-250W MH
LT-WP01-90W	100-277VAC	90W	30K, 40K, 50K, 57K	120	365*230*195mm	250-400W MH
LT-WP01-120W	100-277VAC	120W	30K, 40K, 50K, 57K	120	365*230*195mm	400W MH
LT-WP01-60W-CPT	100-277VAC	36W-48W-60W Selectable	30K-40K-50K Selectable	120	365*230*195mm	175-250W MH
LT-WP01-120W-CPT	100-277VAC	72W-100W-120W Selectable	30K-40K-50K Selectable	120	365*230*195mm	400W MH



CCT & Wattage Selectable

There are allowed 3 different wattage and color temperature settings with simple slide switches, such as 36W-48W-56W and 3000K-4000K-5000K.


Dark Sky Compliant Light Shield

Offer a light shield to get more focused downcast light as opposed to the more exposed and widespread illumination.



Excellent Heat Sink Design

Accelerate heat dissipation on the LEDs to extend the lifespan.



Emergency Backup Available

Outdoor LED Wall Mounted flood lights can provide an emergency solution to the perimeter and security lighting applications.

140 LPW

CERTIFICATE

