

DLC QPL LED WALL PACKS

DESCRIPTION

LED Wall Packs provide commercial & industrial grade high duty die-casting aluminum alloy housing. Tempered glass refractor never becomes yellowish by the time. Powder-coating finish and sealed gasket especially are suitable for outdoor corrosion and wet/damp location. Occupancy sensor can be optional application for building, parking lot lighting, square, road and others.

Many utilities offer lucrative rebates for LMC' lights LED. It is able to accelerate the payback.

CONSTRUCTION & MATERIALS

- Dia-casting aluminum alloy housing, fully sealed to be dirt and bug proof
- Impact-proof and shatter-proof glass refractor
- IP 65 rating waterproof protection
- Polyester powder-coated finish, rust and corrosion proof, stabilized to extreme climate changes without cracking or peeling
- Internal UL approved power supply

MOUNTING AND WIRING

- Mount directly over a standard outlet box or for surface wiring via any of the 3 convenient 3/4 inch threaded conduit entry hubs.

ENVIRONMENTAL SYSTEM

- Outdoor wet/damp location

FINISH

- Bronze (black for option)

ELECTRICAL SYSTEM

- Input voltage 100-277VAC/347-480VAC, 50/60Hz
- ETL/cETL/CE/Rohs, DLC qualified

OPTICAL SYSTEM

- 140 lm/w
- Color temperature: 3000K, 4000K, 5000K, 5700K
- DLC listed as Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires

LIGHTING CONTROL

- Standard 1-10vdc dimming
- Occupancy sensor available
- Emergency backup available

WARRANTY

10 Years Limited

DATA SHEET

Model#	LT-WP01-40W	LT-WP01-60W	LT-WP01-90W	LT-WP01-120W
Rating	40W	57W	89W	120W
Lumen Output	5600 lm	8200 lm	12500 lm	16000 lm
Input Voltage	100-277VAC, 347-480VAC			
L70	>50,000 hrs			
Package	4PCS/19KG/CTN	4PCS/19KG/CTN	4PCS/20KG/CTN	4PCS/22KG/CTN
Carton Size	61X45X55cm	61X45X55cm	61X45X55cm	61X45X55cm
Operating Temp.	-30°C~+50°C			
Store Temp.	-40°C~+60°C			

ORDER INFORMATION

Sample Number: LT-WP01-90W-HV-27K-P-EM

Com.	Family Name	Power	Voltage	CCT	Refractor	Accessories
LT	WP01	40W	Blank=100-277VAC	30K=3000K	Blank=Glass	PC=Photocell
Lightide	Wall Pack #01 series	60W 90W 120W	HV=250-480VAC	40K=4000K 50K=5000K 57K=5700K	P=PC	MS= Motion sensor GS= Grid Shield LS= Light Shield EM= Emergency Backup

Glass Diffuser




PC Diffuser




ACCESSORIES

Grid Shield (WP01-GSA)



Light Shield (WP01-LSA:)



Photocell



Emergency Backup



DIMENSION

