



Product Introduction

Light Efficacy: Up to 160 lumens/watt
 CCT: 3000K, 4000K, 5000K, 5700K
 Finish: Black
 CRI: 80
 Input Voltage: 100-277vac or 347vac
 Dimming: 1-10vdc available
 Battery: Lithium/Li-Fe PO4
 Emergency Time: 90~180 minutes
 Charge times: > 500
 Occupancy sensor available
 Certificate: DLC QPL
 ETL/cETL listed, CE

Features

- Commercial grade
- High-duty die-casting aluminum alloy case
- IP 65 rating for Indoor or outdoor wet/damp location
- Shock-proof polycarbonate diffuser/lens with beam angle 60/90/120 deg.
- Suitable for conduit/Suspended Mounted
- Emergency Backup 90~180 minutes
- Occupancy motion bi-level sensor/photocell
- 5 years warranty

Specification

Model#	Power	Efficacy	Voltage	Equv.	Battery
LT-UBA320-100W	100W	140 -160 LPW	100-277vac	400W MH	15W/90minutes
LT-UBA320-150W	150W	140 -160 LPW	100-277vac	600W MH	20W/90minutes
LT-UBA400-200W	200W	140 -160 LPW	100-277vac	1000W MH	20W/90minutes
LT-UBA400-240W	240W	140 -160 LPW	100-277vac	1500W MH	20W/90minutes

Order Information

For example: LT-UBA320-150W-HV-30K-PC-EM

Company	Family Name	Wattage	Voltage	CCT	Accessory
LT	UBA320	100W	Std.=100-277VAC	30K=3000K	PC=Photocell
		150W	HV=347VAC	40K=4000K	MS= Motion Sensor
	UBA400	200W		50K=5000K	EM=Emergency backup
		240W		57K=5700K	DM= 1-10VDC Dimming

