MODULE DESIGN

FLOOD LIT



Built to Last, Shine Brighter

DLC CERTIFICATE | ETL CERTIFICATE | ENEC CERTIFIED | CB CERTIFIED | SAA CERTIFIED | CE CERTIFIED | ROHS | 190 LPW | IP66 | 5 YEARS WARRANTY | IK10 | LM79 | LM80

- Input: 100-277vac, 200-480vac
- 160 | 175 | 190 lumens per watt for options.
- Waterproof IP66 Rated
- Marine grade aluminum housing
- Shatter-proof PC cover
- Premium Chip – LM80 certified
- Standard Separate 6-10KV surge protection device to avoid early failure. 20KV available
- Rotatable module +/- 25°
- Rotatable 270° for Yoke mount bracket
- Impact rated IK10
- Glare Rating GR<45
- Unique Lens Design: 10°, 15°, 20°, 40°, 60°, 90°, 140°x100°
- 5 years Warranty
- Listings– DLC, ENEC, ETL/cETL, CE & RoHs, TUV, CB, FCC and SAA

Model#	Wattage	Light Output (max)	Input	SPD	L90B10
LT-HPSD-100W	100 Watt	19,000 lumens	100-277vac	6KV	>100, 000 HRS
LT-HPSD-200W	200 Watt	38,000 lumens	100-277vac	6KV	>100, 000 HRS
LT-HPSD-300W	300 Watt	57,000 lumens	100-277vac	Extra 10KV	>100, 000 HRS
LT-HPSD-400W	400 Watt	76,000 Lumens	100-277vac	Extra 10KV	>100, 000 HRS
LT-HPSD-480W	480 Watt	88,800 Lumens	100-277vac	Extra 10KV	>100, 000 HRS
LT-HPSD-600W	600 Watt	114,000 Lumens	100-277vac	Extra 10KV	>100, 000 HRS
LT-HPSD-800W	800 Watt	144,000 Lumens	100-277vac	Extra 10KV	>100, 000 HRS
LT-HPSD-1000W	1000 Watt	185,000 Lumens	100-277vac	Extra 10KV	>100, 000 HRS
LT-HPSD-1200W	1200 Watt	222,000 Lumens	100-277vac	Extra 10KV	>100, 000 HRS
LT-HPSD-1500W	1440 Watt	266,400 Lumens	100-277vac	Extra 10KV	>100, 000 HRS