

LT-TPA series

# LED VAPOR TIGHT LIGHTS



## **GOOD CONSTRUCTION**

Shatter-proof Polycarbonate cover and 5VA rating housing

## **FULLY PROOF**

IP 65 waterproof, dust-proof, damp-proof and vapor-proof

## **EASY INSTALLATION**

This LED light comes with chain pendent and surface mount easy installation.

## **EXCELLENT PERFORMANCE**

Full fixture outputs up to 150 lumens per watt. Replacing up to 2X40W CFL fixture by 38W led.

## **ENERGY EFFICIENCY**

In extreme contrast to conventional metal-halides, this flood lights led can bring in 90% of energy savings.

## **POWER OPTION**

20W~ 100W

## **LONG LIFETIME**

At 8 hours daily use, Lightide' vapor tight lights LEDs are rated to last 17 years.

## **5-YEAR WARRANTY**

No-compromise warranty covered.

## **LISTINGS**

DLC, ETL/cETL for wet location

**LightIDE**

# LT-TPA SERIES LED VAPOR TIGHT LIGHTS

LED Vapor Tight Light feature IK08 and 5VA rated shatter-proof polycarbonate housing, which coming with frosty or clear strip cover for option. IP65 rating LED vapor tight light fixtures are suitable for indoor or outdoor wet/damp usage. High lumen output level up to 150 LPW of led vapor tight light fixtures usually are installed for storage areas, warehouses, shops and garages etc.

## Performance

**Output Efficacy:** 130 lm/w (frosted cover)  
150 lumen/watt (clear cover)  
**Input Power:** 20W/38W/50W/80W/100W  
**CRI:** 80  
**CCT:** 3000K, 4000K, 5000K, 6000K, 6500K  
**Finish:** White  
**Input Voltage:** 100-277vac or 347vac  
**Warranty:** 5 years  
**Mounting:** Surface mount, Chain pendent  
**Weight:** 2.0 Kg  
**Dimmable:** 0-10V dim available  
**Certificate :** ETL/cETL certified, CE & RoHs  
DLC premium

## Cover Option

### Clear Strip Cover



**Frosty Cover**



**VAPOR  
SEALED**

### Resistant to:

- ✓ Moisture
- ✓ Dust Particles
- ✓ Extreme Temperatures
- ✓ Condensation
- ✓ Harsh Weather
- ✓ Humidity

## Accessory



**Emergency Backup**



**Motion Sensor  
(0-10vdc dim)**

## Order Information

Sample Number: LT-TPA456-27K-DM-F

Com.	Family Name	Length	Wattage	CCT	Voltage	Control Mode	Bracket	Cover
LT	TPA	2=2FT	20=20W	27K=27000K	Blank=100-277VAC HV= 347VAC	DM=0-10VDC Dim PC= Photocell MS= Motion sensor EM=Emergency Backup	Blanket=Surface mount	F=Frosty C= Clear
Lightide	Vapor Tight Light A Type	4=4FT 8=8FT	36=38W 56=50W 80=80W 100=100W	30K=3000K 40K=4000K 50K=5000K 60K=6000K 65K=6500K				

MORE QUALIFIED PRODUCTS, PLEASE CONTACT

sales@lightideled.com  
https://www.lightideled.com  
Lightide Manufactory Co., Ltd All right reserved.

