

LED Garage & Canopy Light Fixtures 60W

LT-SGSAL-60W (HV)



Features

- Vandal-proof housing
- New slim design shock-proof polycarbonate diffuser
- Glare-free
- Occupancy sensor available
- Parking drive lane safety and building code compliant
- Mount to surfaces or ceilings
- Color uniformity and even light distribution
- Universal voltage operation
- IP65-rated waterproof
- 120 lumen per watt
- ETL/cETL listed, CE & RoHs
- DLC Premium
- 5 years warranty

[Datasheet](#)

[Inquiry Now](#)

Performance		
Model#	LT-SGSAL-60W	LT-SGSAL-60W-HV
Input Voltage	100-277 VAC	347-48VAC
Input Power	58 watts	58 watts
Power Factor	>0.9	>0.9
Delivered Lumens (lm)	6800	6800
Efficacy (lm/W)	117.3	117.3
Color Rendering Index (CRI)	70	70
Color Temperature (CCT)	3000K, 4000K, 5000K, 5700K	3000K, 4000K, 5000K, 5700K
Beam Angle	120 ⁰	120 ⁰
Equivalent Wattage	175~250 Watts MH	175~250 Watts MH
Dimming Control	Available	Available
Dimensions		
Product Length (Inches)	12.4	12.4
Product Width (Inches)	12.4	12.4
Product Height (Inches)	5.31	5.31
Gross Weight (lbs.)	9.45	9.45
Material		
Housing	High-duty aluminum alloy	High-duty aluminum alloy
Diffuser	Polycarbonate	Polycarbonate
Finish	Bronze	Bronze
Waterproof	IP65	IP65
Longevity		
L70 Life (Hours)	50000	50000
Warranty (Years)	5	5
Certificate		
	DLC Premium, ETL/cETL	ETL/cETL
	CE, RoHs	CE, RoHs
Available Accessories		
Emergency Backup	Available	Available
Motion Sensor	Available	Available
Daylight Sensor	Available	Available