



## CONSTRUCTION & MATERIALS

- Dia-casting aluminum alloy housing, fully sealed to be dirt and bug proof
- Shock-proof polycarbonate refractor with UV inhibitors
- IP 65 rating waterproof protection
- Polyester powder-coated finish, rust and corrosion proof, stabilized to extreme climate changes without cracking or peeling
- Internal UL approved Meanwell or equivalent power supply

## MOUNTING AND WIRING

- Three 3/4" mounting holes plus one on top for mounting. One installation bracket with screws are supplied in package

## ENVIRONMENTAL SYSTEM

- Outdoor wet/damp location

## FINISH

- Bronze

## ELECTRICAL SYSTEM

- Input voltage 100-277VAC/347-480VAC, 50/60Hz
- ETL/cETL/CE/Rohs, DLC qualified

## OPTICAL SYSTEM

- LM 80 SMD LED
- Color temperature: 3000K, 4000K, 5000K, 5700K.
- Extremely wide lighting distribution

## LIGHTING CONTROL

- 0-10vdc/PWM dimming
- Motion sensor
- Photocell

## WARRANTY

5 Years

# LT-SGSAL SERIES LED GAS STATION CANOPY LIGHT

LED Canopy luminaire provides die-casting aluminum alloy heat sink and high shock-proof polycarbonate refractor. Powder-coating finished housing and sealed gasket especially are suitable for outdoor corrosion and wet/ damp location. Motion sensor and photocell sensor can be applied for parking garage lighting, warehouse, mail and others.

## Performance

**Light Output:** 4,800- 10,500 lumens  
**Input Power:** 40/60/90 watts  
**CRI:** 70  
**CCT:** 3000K, 4000K, 5000K, 5700K  
**Finish:** Bronze  
**Input Voltage:** 100-277vac or 250-480vac  
**Warranty:** 5 years  
**Mounting:** Surface mount  
**Weight:** 4.2 Kg  
**Dimming:** 0-10V available  
**Certificate :** ETL/CETL , CE/RoHs  
 DLC premium

## Diffuser Option




**Low Profile  
(SGSAL series)**




**High Profile  
(SGSAH series)**

## Dimension



LT-SGSAL-40W



LT-SGSAL-60W  
LT-SGSAL-90W

## Accessories

Photocell



Motion sensor



## Order Information

Sample Number: LT-SGSAL-40W-HV-30K-DM

Com.	Family Name	Cover Type	Watts	Voltage	CCT	Finish	Control Mode
LT	SGSA	H=High L=Low	40W 60W 90W	Blank=100-277VAC HV=250-480VAC	30K=3000K 40K=4000K 50K=5000K 57K=5700K	Blank=Bronze BK=Black	DM=0-10VDC Dimming PC=Photocell MS= Motion sensor
Lightide	Gas Station Canopy Light						