

○○○○

BUYING GUIDE
VER A1

LED WALL PACK

LIGHTIDE
Lighting Your Value

○○○○

www.lightideled.com | sales@lightideled.com

FEATURES

DLC Certified

DLC qualify for the highest utility rebates.

Warranty

Sell and back them with an excellent 5-10 years warranty

Emergency Solution

Provide reliable backup lighting when power outages.



SEMI CUT-OFF

LT-WP01 Series

LED Wall Pack lights provide a high-efficient 140 LPW to the perimeter and security lighting for commercial and residential applications. In addition, DLC-qualified LED wall-mounted light fixtures are able to accelerate the payback.

- **Wide Input Voltage - 100-277 or 120-347vac**
- **Excellent Efficacy - 140 lumens per watt**
- **Std.1-10vdc Dimming**
- **Emergency Battery Backup is available.**
- **Work Temperature: -40°F ~+140°F**

ORDERING GUIDE

Com.	Series	Rated	Voltage	CCT	Option	Duration	Cover
LT	WP01	40W	Blank=100-277vac	30K =3000K	DM=1-10VDC	STD.=90MIN.	Blank=Glass
		60W	HV =200-480vac	40K=4000K	PC=Photocell	2H=120MIN.	P=Plastic
		90W		50K=5000K	MS=Motion	3H=180MIN.	
		120W		57K= 5700K	EM=Emergency		



Dark Sky
Compliant
Shield



Emergency
Backup



Wire Guard





FULL CUT-OFF

LT-WPCT/A Series

Outdoor Full Cutoff LED wall packs feature trapezoid style and dusk to dawn work mode. 120 LPW of LED wall pack for 400W MH Equiv. In addition, exterior led wall light fixtures can work great for pathway and building perimeter lighting. Moreover, these wall-mounted LED lights are also fit for illumination of entry and exit ways enabling security lighting.

- Wide Input Voltage - 100-277 or 120-347vac
- Excellent Efficacy - 120 lumens per watt
- Emergency Backup is available.

ORDERING GUIDE

Com.	Series	Rated	Voltage	CCT	Option	Duration
LT	WPCA	40W	Blank=100-277vac	30K =3000K	DM=1-10VDC	STD.=90MIN.
	WPCT	60W	HV =200-480vac	40K=4000K	PC=Photocell	2H=120MIN.
		80W		50K=5000K	MS=Motion	3H=180MIN.
		100W		57K= 5700K	EM=Emergency	



LT-WPCT Series



Dusk-Dawn



LT-WPCA Series





ROTATABLE

LT-WPSLA Series (Gen 2)

Outdoor LED Wall Pack Lights combine rotatable styling and unique optical design (90°X65°) for floodlighting and security lighting. In addition, the design separating the heat dissipation system from drivers can keep more lifespan and guarantee long-time safety operations.

- Excellent Performance - 124 LPW.
100-120W LED wall pack 400W equivalent.
- Rotatable Style - 0-90 degrees of direction adjusted.
- Photocell available

ORDERING GUIDE

Com.	Series	Rated	Voltage	CCT	Option	Finish
LT	WPSLA	35W	Blank=100-277vac	30K =3000K	DM=1-10VDC	Blank=Brown
		60W	HV =200-480vac	40K=4000K	PC=Photocell	WH= White
		80W		50K=5000K	MS=Motion	
		100W		57K= 5700K		



Dusk-Dawn



Adjustable





POWER & CCT TUNABLE

LT-WPCQ Series (Quarter-sphere)

Outdoor wall mount LED light fixtures feature a quarter-sphere style of wall packs. And they can be power selectable ranges of 60-80-100 watts and CCT selectable ranges of 3000K-4000K-5000K.

- 120 lumens per watt. 400W MH equivalent by 100W led Wall Packs.
- CCT & Power Tunable
- Rotatable 38 degree from semi cutoff to full cutoff
- Dusk-Dawn & Motion Sensor available
- Die-casting housing + Shatter-proof PC/Glass lens

ORDERING GUIDE

Com.	Series	Rated	Voltage	CCT	Option	Duration	Cover
LT	WPCQ	80CP=60W-80W-100W Tunable	Blank=100-277vac	30K =3000K	DM=1-10VDC	STD.=90MIN.	Blank=Glass
		06=60W	HV=200-480vac	40K=4000K	PC=Photocell	2H=120MIN.	P=Plastic
		08=80W		50K=5000K	MS=Motion	3H=180MIN.	
		10=100W		57K= 5700K	EM=Emergency		





MINI STYLE

LT-WP02 (S) Series

LED mini wall mounted lights with photocell work great for pathway and building perimeter lighting. And it's a perfect choice to be used in parking garages, schools, outdoor walkways, gardens, fences, stairs, patio, driveway, outdoor security lighting, and anywhere that needs great lights.

- Dusk to Dawn
- Excellent Performance - 110 lumens per watt.
- Fully Weatherproof - IP65 rated.
- 12W, 18W, 20W, 25W, 30W

ORDERING GUIDE

Com.	Series	Rated	Profile	CCT	Option	Finish
LT	WP02	12W	S	30K =3000K	PC=Photocell	Blank=Brown
		18W		40K=4000K		WH= White
		20W		50K=5000K		
		25W		57K= 5700K		
		30W				



**LT-WP02-
20W/25W/30W-S**



**LT-WP02-
12W/18W/30W**





ARCHITECTURAL

LT-AF02 Series

LED Outdoor Security Yard Lights offer a photocell for dusk to dawn work mode. In addition, the powder-coating finish assures corrosion resistance and long-lasting aesthetics. And the shatterproof polycarbonate cover can get the IK08 rating.

- Excellent Performance - 130 lumens per watt. Replacing up to 250W MH by 70W LED Lights.
- Pole Mount/ Wall Mount Optional
- Dusk-Dawn: Photocell inside/outside optional

ORDERING GUIDE

Com.	Series	Rated	Voltage	CCT	Option	Mount
LT	AF02	35W	Blank=100-277vac	30K =3000K	PCI=Photocell Inside	PM= Pole Mount
		45W	HV =200-480vac	40K=4000K	PCO=Photocell Outside	WM= Wall Mount
		75W		50K=5000K		
		100W		57K= 5700K		
		120W				
		150W				



Pole Mount Kit



Photocell Outside



Photocell Inside



CHOOSING GUIDE

2

Choose Wattage

40W 100W EQUIV. Up to 4,800 lm	60W 150W EQUIV. Up to 7,200 lm	90W 250W EQUIV. Up to 10,800 lm	120W 250W EQUIV. Up to 14,400 lm
---	---	--	---

4

Choose Accessories

Light shield
wire guard

1

Choose Style

Semi Cutoff
Full Cutoff
Mini Style

3

Choose Options

VOLTAGE	CCT	CONTROL	COVER
100-277vac	3000K	1-10vdc dim	Glass
347vac	4000K	Motion	plastic
480 vac	5000K	Photocell	
	5700K	Emergency	



CONTACT

*We look forward to working
with you*



Sanjia Industrial Zone, Nanhai,
Foshan, Guangdong, China



+86-755-8383-7000



www.lightideled.com



sales@lightideled.com

