

MINI LED WALL PACK (WP02 Series)

DESCRIPTION

MINI LED Wall Pack Light provides small profile dia-casting aluminum alloy heat sink and shatter-proof PC diffuser. Powder-coating finished housing and sealed gasket especially are suitable for outdoor corrosion and wet/ damp location. Photozell sensor can be optional application for entrance, building, parking lot lighting, square, road and others.

CONSTRUCTION & MATERIALS

- Dia-casting aluminum alloy housing, fully sealed to be dirt and bug proof
- Impact-proof and shatter-proof polycarbonate diffuser
- IP 65 rating waterproof protection
- Polyester powder-coated finish, rust and corrosion proof, stabilized to extreme climate changes without cracking or peeling
- Internal UL approved power supply

MOUNTING AND WIRING

- Mount directly over a standard outlet box or for surface wiring via any of the 3 convenient 3/4 inch threaded conduit entry hubs.

ENVIRONMENTAL SYSTEM

- Outdoor wet/damp location

FINISH

- Bronze (white option)

ELECTRICAL SYSTEM

- Input voltage 100-277VAC, 50/60Hz
- ETL/cETL/CE/RoHs, DLC QPL

OPTICAL SYSTEM

- LM 80 SMD LED
- Color temperature: 3000K, 4000K, 5000K, 5700K
- DLC listed as Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires

LIGHTING CONTROL

- Occupancy daylight sensor

WARRANTY

5 Years

DATA SHEET

Model#	LT-WP02-12W	LT-WP02-18W	LT-WP02-30W
LED Power	12W	18W	26W
Lumen Output	1400lm	2160 lm	3120 lm
Input Voltage	100-277VAC		
Power Factor	0.90		
CRI	>70		
L70	>50,000 hrs		
Operating Temp.	-30°C~+50°C		
Store Temp.	-40°C~+60°C		
Package	CTN: 64X39X32CM, 12.5Kg/CTN. 10PCS/CTN		
Installation	Recessed outlet box or wall surface		

ORDER INFORMATION

Sample Number: LT-WP02-18W-27K-PC

Com.	Family Name	Wattage	CCT	Control Mode
LT	WP02	12W	30K=3000K	PC=Photocell
Lightide	MINI Wall Pack Type 02 series	18W	40K=4000K	MS= Motion sensor
		30W	50K=5000K	
			60K=6000K	



White Option



DIMENSION

