



CONSTRUCTION & MATERIALS

- Cold Precision Forging Process aluminum alloy
- IP 66 waterproof protection for wet and damp location usage
- Polyester powder-coated finish, rust and corrosion proof, stabilized to extreme climate changes without cracking or peeling
- Built-in J-Box
- Lithium battery
- 90 min. of emergency work time
- 24 hrs charge time
- L70 > 50,000 hrs

INSTALLATION MOUNTING

- Pendant

Finish

- White/Black

CERTIFIED GUARANTEE

- DLC qualified
- ETL/cETL listed
- Conforms to UL 924
- NFPA 101 Compliant

ELECTRICAL SYSTEM

- Widely Input voltage: 100-277VAC/347VAC
- Power chosen from 100W, 150W, 200W,

MANY OPTICAL SYSTEM OPTION

- Lens of Beam angle: 60°, 90° and 120°
- Reflector: 60° and 90°
- Output 140 lm/w

LONG WARRANTY

- 5 Years

LT-UBA SERIES UFO LED High Bay Light Battery Backup

UFO LED High Bay Light features high lumen efficacy 140+ LPW of SMD LED for any application requiring maximum performance and minimum maintenance. The rugged, cold-forging aluminum housing and sealed and gasket optics compartment combine to make LED light virtually impenetrable to contaminants. 90 min. of battery backups for warehouse, parking lot lighting, plant lighting, supermarket, mail and other lighting applications.

Performance

Output Efficacy: 140 LPW
Input Power: 100W, 150W, 200W, 240W
CRI: 70
CCT: 3000K, 4000K, 5000K, 5700K, 6500K
Finish: White or Black
Input Voltage: 100-277vac
Warranty: 5 years
Emergency Battery: 90 Min. time
Weight: 6.0-8.0 Kg
Certificate : ETL/cETL, CE & RoHS
 UL 924, CSA C22.2 NO. 141
 CEC Title 20,
 NFPA101 compliant

Reflector Optional



Reflector

Battery



Intelligent emergency detection function:
 The emergency high bay light can switch to emergency mode automatically when power is off.
 Overcharge protection, over-discharge protection, short-circuit protection

Detail

Illumination with an average of 1-footcandle and a minimum of 0.1-footcandle when installed according to guidelines



Each emergency fixture provides at least 90 minutes of outdoor/indoor

Order Information

Sample Number: LT-UBA320A-150W-27K-EM-2H

Com.	Family Name	Size	Wattage	CCT	Voltage	Control Mode	Work Time
LT	UBA	280A	100W	27K=2700K	Blank=100-277VAC	DM=0-10VDC Dim	Blank=90 minutes
Lightide	UFO Bay Light A Type	320A	150W	30K=3000K	HV= 347VAC	PS= Photocell	2H=120 minutes
		400A	200W	40K=4000K		MS= Motion sensor	3H=180 minutes
			240W	57K=5700K 65K=6500K		EM=Emergency Kit	

MORE QUALIFIED PRODUCTS, PLEASE CONTACT

sales@lightideled.com
<https://www.lightideled.com>
 Lightide Manufacturing Co., Ltd All right reserved.

