

ARCHITECTURAL FLOOD LIT



- Input: 100-277Vac or 10-30Vdc
- 140/150/170 lumens per watt for options.
- Remote control for motion sensor
- ADJ. CCT & Wattage
- High-duty die-casting aluminum heat sink housing, fully sealed to be dirt and bug proof i Impact-proof and shatter-proof PC cover
- IP 66 rating waterproof protection
- Various beam angle 30, 60, 90, 120 deg. options
- 7-year Warranty
- ETL/cETL, CE & RoHS



Model# LT-FLHW-TPS
Tripod for 1* floodlight
60-150cm Height



Model# LT-FLHW-TPD
Tripod for 2* floodlight
60-150cm Height



Model#	Wattage	Light Output	CCT	Dimension
LT-FLHW-20W	20 Watt	3,400 lumens	3CCT, 3000K-6500K	160*144*30.5 MM
LT-FLHW-50W	50 Watt, ADJ. 25W-38W-50W	8,920 Lumens	3CCT, 3000K-6500K	192*172*37 MM
LT-FLHW-70W	70 Watt, ADJ. 35W-50W-70W	11,920 Lumens	3CCT, 3000K-6500K	240*200*45 MM
LT-FLHW-100W	100 Watt, ADJ. 50W-75W-100W	16,920 Lumens	3CCT, 3000K-6500K	280*250*45 MM
LT-FLHW-150W	150 Watt, ADJ. 75W-110W-150W	24,920 Lumens	3CCT, 3000K-6500K	346*312*54 MM
LT-FLHW-200W	200 Watt, ADJ. 100W-150W-200W	33,920 Lumens	3CCT, 3000K-6500K	346*312*54 MM
LT-FLHW-240W	240 Watt, ADJ. 120W-180W-240W	40,920 Lumens	3CCT, 3000K-6500K	380*350*63 MM
LT-FLHW-300W	300 Watt, ADJ. 150W-225W-300W	50,920 Lumens	3CCT, 3000K-6500K	380*350*72 MM
LT-FLHW-400W	400 Watt	56,020 Lumens	3000K-6500K	480*430*105 MM
LT-FLHW-500W	500 Watt	70,920 Lumens	3000K-6500K	480*430*105 MM