

LED WALL PACK LIGHT (2ND-GEN)

DESCRIPTION

LED Wall Pack Lights provides new heat sink design made of die-casting aluminum alloy and polycarbonate lens coming with full cutoff style. Powder-coating finished housing and sealed gasket for Ip65 rating especially are suitable for outdoor corrosion and wet/ damp location. Motion sensor and photocell sensor can be optional application for building, parking lot lighting, square, road and others.

CONSTRUCTION & MATERIALS

- ◆ High-duty -die-casting aluminum housing, fully sealed to be dirt and bug proof
- ◆ Impact-proof glass cover
- ◆ IP 65 rating waterproof protection
- ◆ Bronze polyester powder-coated finish, rust and corrosion proof, stabilized to extreme climate changes without cracking or peeling
- ◆ Built-in UL driver
- ◆ Full cutoff style

EMERGENCY OPTION

- ◆ Lithium/ Li-Fe PO4/Ni-MH
- ◆ UL 924 & CEC title 20 compliant
- ◆ Output: 480 lumens
- ◆ Charge time: 24 hrs
- ◆ Duration: 90 minutes
- ◆ Charge cycle: >500 times

MOUNTING AND WIRING

- ◆ Mount directly over a standard outlet box or for surface wiring via any of the 4 convenient 3/4 inch threaded conduit entry hubs.

ENVIRONMENTAL SYSTEM

- ◆ Outdoor wet/damp location

ELECTRICAL SYSTEM

- ◆ Input voltage 100-277VAC
- ◆ ETL/cETL,
- ◆ CE/RoHS.

OPTICAL SYSTEM

- ◆ 120 lm/w output efficacy
- ◆ Color temperature: 3000K, 4000K, 5000K and 5700K. Other color temperature available for special order, consult factory for lead time.
- ◆ 120° beam angle

LIGHTING CONTROL

- ◆ 0/1-10vdc dimming available

FINISH

- ◆ Bronze (default)
- ◆ Black or White for option

WARRANTY


- ◆ 5 Years

STANDARD

- ◆ EN61347-1, EN61347-2-13, EN60598-2-1, EN60598-1
- ◆ UL 924, UL 1598, CAN/CSA -C.22.2 NO. 250.0,



DIMENSION



PACKAGE

Model#	G. W.	Carton Size
LT-WPCA-35W/60W/80W	7.2 lbs	37X20X26 cm

DATA SHEET

Model#	LT-WPCA-35W	LT-WPCA-60W	LT-WPCA-80W
Rating	35W	62W	80W
Lumen Output	4245 lm	7500 lm	9700 lm
Input Voltage	100-277VAC, 200-480VAC		
Power Factor	0.98at 100VAC 0.90 at 277VAC/200-480VAC		
LED & CCT	3000K/4000K/5000K/5700K		
CRI	>70		
L70	>50,000 hrs		
Operating Temp.	-30°C~+50°C		
Certification	ETL/cETL		

ORDER INFORMATION

Sample Number: LT-WPCA-80W-30K-PC-EM

Com.	Family Name	Wattage	Voltage	CCT	Finish	Control Mode
LT	WPCA	35W 60W 80W	Blank=100-277VAC HV=200-480VAC	30K=3000K 40K=4000K 50K=5000K 57K=5700K	Blank=Bronze WH=White	DM=0-10VDC Dimming PC=Photocell MS= Motion sensor EM= Emergency Battery Backup