

ROUND LED POST TOP



Light Up Your Nights Smartly

FEATURE

- Wide input: 100-277vac, 120-347vac (DLC)
- 140-170 lumens per watt.
- ADJ. Wattage & CCT
- LED Distribution- Type II, III, IV and V
- Easy Installation – suitable for 3" pole mounted
- High-duty die-casting aluminum housing.
- Glass cover
- Size: DIA. 430X489 MM
- IP66 Rated, IK08
- 5 Year Warranty
- DLC, ETL/CETL,
- ENEC, CB, SAAA, CE, RoHS



Model#	Wattage	Light Output	Input	Equivalent	CCT
LT-PTE030	30 Watt	5,200 lumens	120-277vac	75-100 Watt HPS/MH	30K,40K,50K, 57K, 3CT
LT-PTE040	40 Watt	6,920 Lumens	120-277vac	100 Watt HPS/MH	30K,40K,50K, 57K, 3CT
LT-PTE050	50 Watt	8,200 lumens	120-277vac	150 Watt HPS/MH	30K,40K,50K, 57K, 3CT
LT-PTE080	80 Watt	9,600 lumens	120-277vac	250 Watt HPS/MH	30K,40K,50K, 57K, 3CT
LT-PTE100	100 Watt	15,200 lumens	120-277vac	400 Watt HPS/MH	30K,40K,50K, 57K, 3CT
LT-PTE150	150 Watt	20,920 Lumens	120-277vac	400 Watt HPS/MH	30K,40K,50K, 57K, 3CT